

Order Code: XCNC6X1

1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable

**Technical Data****General**

Luminaire Wattage (W)	35W/44W/53W/62W
Weight (kg)	2.21
Operating Temperature (ta °C)	5° to 25°

Light Output

Lumens (lm)	6000 to 10400
Efficacy (lm/W)	171

LED

CRI	80
Macadam Ellipses	8

Driver

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	155 to 164Vdc

Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- Modular EMG & Sensor option available
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [microwave sensor](#) for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation

Order Code: XCNC6X1

1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable

Dimensions

A (mm)	1875
B (mm)	80
C (mm)	95
Fix	600

Line Drawing

