

**Order Code: XCNC6X1M3**

1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency

**Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [35W/44W/53W/62W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

**Construction**

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [microwave sensor](#) for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

**Installation Notes**

Conduit and BESA fixing points for end or rear cable entry  
Loop in/out push-fit terminal block for quick installation

**Technical Data****General**

Luminaire Wattage (W)	35W/44W/53W/62W
Weight (kg)	2.81
Operating Temperature (ta °C)	5° to 25°

**Light Output**

Lumens (lm)	6000 to 10400
Efficacy (lm/W)	170

**Electrical**

Rated Input Current (A)	0.17 to 0.29
Power Factor (pf)	0.92 to 0.96
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	200
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

**LED**

CRI	80
Macadam Ellipses	8

**Driver**

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	155 to 164Vdc

**Emergency**

Emergency Lumen Operating	327
Emergency Wattage (W)	2

**Order Code: XCNC6X1M3**

1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency

## Dimensions

A (mm)	1875
B (mm)	80
C (mm)	95
Fix	600

## Line Drawing

