## xcite LED Lighting

## **Data Sheet**

Order Code: XCPL9WW

9W - Porch Light LED - Fixed Output - 3000K



#### **Features**

- Suitable for exterior walls and entrance areas
- Low energy LED module for reduced running costs
- Up to 61 lumens per watt efficacy

#### Construction

- Die-cast aluminium body finished in Anthracite grey
- Frosted polycarbonate diffuser
- Supplied as standard with warm white [3000K] LED

#### **Installation Notes**

Fixed via rear wall mounting plate with cable entry and wired via 3-way termination block















#### **Technical Data**

100 milati Bata				
General		Electrical		
Luminaire Wattage (W)	9	Rated Input Current (A)	0.04	
Weight (kg)	0.70	Power Factor (pf)	0.94	
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	198-264	
124.0		Inrush Current Peak (A)	13	
Light Output Lumens (Im)	550	Surge Protection (kV)	1	
Efficacy (lm/W)	61	Conductor Size (mm)	0.5-1.5	
		Terminal Type	PIANO 3	
LED				
CCT (K)	3000			
CRI	84			
Driver				
Driver Current (mA)	350			
Forward Voltage (V)	21			

# xcite LED Lighting

### **Data Sheet**



Order Code: XCPL9WW

9W - Porch Light LED - Fixed Output - 3000K

#### **Dimensions**

A (mm)	180
B (mm)	135
Dia. (mm)	90

### Line Drawing



