

**Order Code: XCRL100DLPC**

100W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

**Features**

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 2 sizes
- Available in 3 different outputs
- Photocell option available
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 120 lumens per watt efficacy

**Construction**

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED

**Technical Data****General**

Luminaire Wattage (W)	100
Weight (kg)	5.20
Operating Temperature (ta °C)	-20 to 25

**Light Output**

Lumens (lm)	12000
Efficacy (lm/W)	120

**LED**

CCT (K)	6000
CRI	70
Macadam Ellipses	3

**Driver**

Driver Current (mA)	464
Forward Voltage (V)	42.9

**Electrical**

Rated Input Current (A)	0.65
Power Factor (pf)	0.97
Input Voltage Range (VAC)	100-240
Inrush Current Peak (A)	52.5
Surge Protection (kV)	6
Conductor Size (mm)	1
Terminal Type	Bare wire

### Order Code: XCRL100DLPC

100W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

#### Dimensions

A (mm)	715
B (mm)	280
C (mm)	138

#### Line Drawing

