xcite LED Lighting

Data Sheet



0.2

Bare wire

Order Code: XCRL30DL

30W - Outdoor Road Lantern - IP65 - 6000K



Features

- · Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 3 different outputs
- Photocell option available
- · Available in 2 sizes
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 120 lumens per watt efficacy

Construction

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED











Technical Data

General			Electrical
Luminaire Wattage (W)	30	Rated Input Current (A)	
Weight (kg)	2.26	Power Factor (pf)	
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	
Light Output		Inrush Current Peak (A)	
Light Output Lumens (Im)	3600	Surge Protection (kV)	
Efficacy (Im/W)	120	Conductor Size (mm)	
Linday (III)		Terminal Type	
LED			
CCT (K)	6000		
CRI	70		
Macadam Elipses	3		
Driver			
Driver Current (mA)	135		
Forward Voltage (V)	40.3		



xcite LED Lighting

Data Sheet



Order Code: XCRL30DL

30W - Outdoor Road Lantern - IP65 - 6000K

Dimensions

A (mm)	500
B (mm)	212
C (mm)	68

Line Drawing





