

**Order Code: XCRL30DLPC**

30W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K



**Features**

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 3 different outputs
- Photocell option available
- Available in 2 sizes
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 120 lumens per watt efficacy

**Construction**

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	30	Rated Input Current (A)	0.2
Weight (kg)	2.46	Power Factor (pf)	0.88
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	120-240
<b>Light Output</b>		Inrush Current Peak (A)	6.35
Lumens (lm)	3600	Surge Protection (kV)	4
Efficacy (lm/W)	120	Conductor Size (mm)	1
<b>LED</b>		Terminal Type	Bare wire
CCT (K)	6000		
CRI	70		
Macadam Elipses	3		
<b>Driver</b>			
Driver Current (mA)	135		
Forward Voltage (V)	40.3		

**Order Code:** XCRL30DLPC

30W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

### Dimensions

A (mm)	500
B (mm)	212
C (mm)	118

### Line Drawing

