

Order Code: XCRL60DLPC

60W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K



Features

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 3 different outputs
- Photocell option available
- Available in 2 sizes
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 112 lumens per watt efficacy

Construction

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	60	Rated Input Current (A)	0.4
Weight (kg)	2.46	Power Factor (pf)	0.94
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	120-240
		Inrush Current Peak (A)	33.2
		Surge Protection (kV)	4
		Conductor Size (mm)	1
		Terminal Type	Bare wire
Light Output			
Lumens (lm)	6700		
Efficacy (lm/W)	112		
LED			
CCT (K)	6000		
CRI	70		
Macadam Ellipses	3		
Driver			
Driver Current (mA)	270		
Forward Voltage (V)	39.9		

Order Code: XCRL60DLPC

60W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

Dimensions

A (mm)	500
B (mm)	212
C (mm)	118

Line Drawing

