

**Order Code: XCRLLX1**

X1 Road Lantern - 3000K-5000K + Wattage Selectable - Large

**Features**

- CCT [3000K/4000K/5000K] adjustable via 3-way selector switch
- Wattage [110W/120W/135W] adjustable via selector switch
- Up to 141 lumens per watt efficacy

**Construction**

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [42.6mm to 60mm]

**Installation Notes**

Wired via screwless connector inside main body  
Loop in/out push-fit terminal block for quick installation

**Technical Data****General**

Luminaire Wattage (W)	110W/120W/135W
Weight (kg)	3.58
Operating Temperature (ta °C)	0° to 25°

**Light Output**

Lumens (lm)	15800 - 18300
Efficacy (lm/W)	141

**LED**

CRI	80
Macadam Ellipses	1.8 to 4.4

**Driver**

Driver Current (mA)	2900
Forward Voltage (V)	43.7 to 46.3

**Electrical**

Rated Input Current (A)	0.49 to 0.61
Power Factor (pf)	0.95 to 0.97
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	300
Surge Protection (kV)	1kV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

Order Code: XCRLLX1

X1 Road Lantern - 3000K-5000K + Wattage Selectable - Large

## Dimensions

A (mm)	555
B (mm)	210
C (mm)	90

## Line Drawing

