

Order Code: XCROLLX1PC

X1 Road Lantern - Large - CCT [3000K/4000K/5000K] + Wattage Selectable + Photocell



Features

- CCT adjustable via selector switch [3000K/4000K/5000K]
- Wattage adjustable via selector switch [110W/120W/135W]
- Up to 141 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [42.6mm to 60mm]

Installation Notes

Wired via screwless connector inside main body
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	110W/120W/135W	Rated Input Current (A)	0.49 to 0.61
Weight (kg)	3.72	Power Factor (pf)	0.95 to 0.97
Operating Temperature (ta °C)	0° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output		Inrush Current Peak (A)	300
		Surge Protection (kV)	1KV
Lumens (lm)	15800 to 18300	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	141	Terminal Type	4 pole piano key
LED			
CCT (K)	3000K/4000K/5000K		
CRI	80		
Macadam Ellipses	1.8 to 4.4		
Driver			
Driver Current (mA)	2900		
Forward Voltage (V)	43.7 to 46.3		

Order Code: XCRLX1PC

X1 Road Lantern - Large - CCT [3000K/4000K/5000K] + Wattage Selectable + Photocell

Dimensions

A (mm)	555
B (mm)	210
C (mm)	158

Line Drawing

