

Order Code: XCRLLX1PC

3000K-5000K + Wattage Selectable + Photocell

**Features**

- CCT [3000K/4000K/5000K] adjustable via 3-way selector switch
- Wattage [110W/120W/135W] adjustable via selector switch
- Up to 141 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [42.6mm to 60mm]

Installation Notes

Wired via screwless connector inside main body
Loop in/out push-fit terminal block for quick installation

Technical Data**General**

Luminaire Wattage (W)	110W/120W/135W
Weight (kg)	3.72
Operating Temperature (ta °C)	0° to 25°

Light Output

Lumens (lm)	15800 - 18300
Efficacy (lm/W)	141

LED

CRI	80
Macadam Ellipses	1.8 to 4.4

Driver

Driver Current (mA)	2900
Forward Voltage (V)	43.7 to 46.3

Electrical

Rated Input Current (A)	0.49 to 0.61
Power Factor (pf)	0.95 to 0.97
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	300
Surge Protection (kV)	1kV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

Order Code: XCRLLX1PC

3000K-5000K + Wattage Selectable + Photocell

Dimensions

A (mm)	555
B (mm)	210
C (mm)	158

Line Drawing

