

**Order Code: XCRLSX1**

X1 Road Lantern - 3000K-5000K + Wattage Selectable

**Features**

- CCT [3000K/4000K/5000K] adjustable via 3-way selector switch
- Wattage [40W/50W/60W] adjustable via selector switch
- Up to 149 lumens per watt efficacy

**Construction**

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [42.6mm to 60mm]

**Installation Notes**

Wired via screwless connector inside main body  
Loop in/out push-fit terminal block for quick installation

**Technical Data****General**

Luminaire Wattage (W)	40W/50W/60W
Weight (kg)	2.55
Operating Temperature (ta °C)	0° to 25°

**Light Output**

Lumens (lm)	6000 - 8700
Efficacy (lm/W)	149

**LED**

CRI	80
Macadam Ellipses	2.1 to 4.4

**Driver**

Driver Current (mA)	1090
Forward Voltage (V)	43 to 50

**Electrical**

Rated Input Current (A)	0.19 to 0.27
Power Factor (pf)	0.95 to 0.97
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	60
Surge Protection (kV)	1kV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

## Order Code: XCRLSX1

X1 Road Lantern - 3000K-5000K + Wattage Selectable

## Dimensions

A (mm)	480
B (mm)	160
C (mm)	90

## Line Drawing

