

Order Code: XCRLSX1PC

X1 Road Lantern - CCT [3000K/4000K/5000K] + Wattage Selectable + Photocell



Features

- CCT adjustable via 3-way selector switch [3000K/4000K/5000K]
- Wattage adjustable via selector switch [40W/50W/60W]
- Up to 149 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [42.6mm to 60mm]

Installation Notes

Wired via screwless connector inside main body
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	40W/50W/60W	Rated Input Current (A)	0.19 to 0.27
Weight (kg)	2.68	Power Factor (pf)	0.95 to 0.97
Operating Temperature (ta °C)	0° to 25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	60
		Surge Protection (kV)	1KV
		Conductor Size (mm)	0.5 to 2.5
		Terminal Type	4 pole piano key
Light Output			
Lumens (lm)	6000 to 8700		
Efficacy (lm/W)	149		
LED			
CCT (K)	3000K/4000K/5000K		
CRI	80		
Macadam Elipses	2.1 to 4.4		
Driver			
Driver Current (mA)	1090		
Forward Voltage (V)	43 to 50		

Order Code: XCRLSX1PC

X1 Road Lantern - CCT [3000K/4000K/5000K] + Wattage Selectable + Photocell

Dimensions

A (mm)	480
B (mm)	160
C (mm)	158

Line Drawing

