

Order Code: XCRP12650CW
50W - Recessed Edge-lit Panel - 1200mm x 600mm - 5000K



3000K 4000K 5000K 6000K 30,000 HOURS 3YRS WARRANTY IK03

- Features
- Ideal for retrofit of existing T5 or T8 fixtures
  - Suitable for offices and schools
  - 2 sizes available with 2.5mm light guide
  - Compatible with Panel Frame and Surface Panel Frame
  - 3 hours emergency maintained with compatible conversion box Emergency Kit
  - Up to 100 lumens per watt efficacy
- Construction
- Extruded aluminium frame
  - High performance opal TP[b] diffuser
  - Plug and play driver
  - Emergency option available
  - Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]

Technical Data

General		Electrical	
Luminaire Wattage (W)	50	Rated Input Current (A)	0.22
Weight (kg)	5.30	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	15.6
Lumens (lm)	5000	Surge Protection (kV)	2
Efficacy (lm/W)	100	Conductor Size (mm)	1.5
LED		Terminal Type	2 pole grip wire
CCT (K)	5000		
CRI	80		
Macadam Elipses	4		

**Order Code:** XCRP12650CW  
50W - Recessed Edge-lit Panel - 1200mm x 600mm - 5000K

Dimensions

A (mm)	1195
B (mm)	595
C (mm)	10

Line Drawing

