

**Order Code:** XCRP6630NW

30W - Recessed Edge-lit Panel - 600mm x 600mm - 4000K

**Features**

- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- 2 sizes available with 2.5mm light guide
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

**Construction**

- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Plug and play driver
- Emergency option available
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]

**Technical Data****General**

Luminaire Wattage (W)	30
Weight (kg)	2.75
Operating Temperature (ta °C)	0 to 25

**Light Output**

Lumens (lm)	3000
Efficacy (lm/W)	100

**LED**

CCT (K)	4000
CRI	80
Macadam Ellipses	4

**Electrical**

Rated Input Current (A)	0.13
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	14
Surge Protection (kV)	2
Conductor Size (mm)	1.5
Terminal Type	2 pole grip wire

**Order Code: XCRP6630NW**

30W - Recessed Edge-lit Panel - 600mm x 600mm - 4000K

**Dimensions**

A (mm)	595
B (mm)	595
C (mm)	10

**Line Drawing**