

Order Code: XCRP6630NW

30W - Recessed Edge-lit Panel - 600mm x 600mm - 4000K



Features

- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- 2 sizes available with 2.5mm light guide
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

Construction

- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Plug and play driver
- Emergency option available
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]



Technical Data

General		Electrical	
Luminaire Wattage (W)	30	Rated Input Current (A)	0.13
Weight (kg)	2.75	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	14
		Surge Protection (kV)	2
		Conductor Size (mm)	1.5
		Terminal Type	2 pole grip wire
Light Output			
Lumens (lm)	3000		
Efficacy (lm/W)	100		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		

Order Code: XCRP6630NW

30W - Recessed Edge-lit Panel - 600mm x 600mm - 4000K

Dimensions

A (mm)	595
B (mm)	595
C (mm)	10

Line Drawing

