

**Order Code: XCSBT210NW**

10W - 600mm Batten - 4000K

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Batten fit PIR option available
- Up to 115 lumens per watt efficacy

**Construction**

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



**Technical Data**

**General**

|                               |         |
|-------------------------------|---------|
| Luminaire Wattage (W)         | 10      |
| Weight (kg)                   | 0.50    |
| Operating Temperature (ta °C) | 0 to 25 |

**Light Output**

|                 |      |
|-----------------|------|
| Lumens (lm)     | 1150 |
| Efficacy (lm/W) | 115  |

**LED**

|                 |      |
|-----------------|------|
| CCT (K)         | 4000 |
| CRI             | 80   |
| Macadam Elipses | 4    |

**Electrical**

|                           |                  |
|---------------------------|------------------|
| Rated Input Current (A)   | 0.05             |
| Power Factor (pf)         | 0.9              |
| Input Voltage Range (VAC) | 220-240          |
| Inrush Current Peak (A)   | 8                |
| Surge Protection (kV)     | 1                |
| Conductor Size (mm)       | 1.5              |
| Terminal Type             | 3 pole piano key |

**Order Code:** XCSBT210NW

10W - 600mm Batten - 4000K

### Dimensions

|        |     |
|--------|-----|
| A (mm) | 600 |
| B (mm) | 55  |
| C (mm) | 58  |

### Line Drawing

