# xcite LED Lighting

## **Data Sheet**

Order Code: XCSBT210NWP 10W - 600mm Batten - 4000K - PIR





- · Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 115 lumens per watt efficacy

#### Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral emergency option available
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight





















Macadam Elipses



### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.05
Weight (kg)	0.60	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
1:1.0		Inrush Current Peak (A)	8
Light Output  Lumens (Im)	1150	Surge Protection (kV)	1
Efficacy (lm/W)	115	Conductor Size (mm)	1.5
		Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		

# xcite LED Lighting

## **Data Sheet**



Order Code: XCSBT210NWP 10W - 600mm Batten - 4000K - PIR

#### **Dimensions**

A (mm)	721
B (mm)	55
C (mm)	58

### Line Drawing



