

**Order Code: XCSBT417WW**

17W - 1200mm Batten - 3000K

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Batten fit PIR option available
- Up to 121 lumens per watt efficacy

**Construction**

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	17	Rated Input Current (A)	0.08
Weight (kg)	0.90	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	8
Light Output		Surge Protection (kV)	1
Lumens (lm)	2050	Conductor Size (mm)	1.5
Efficacy (lm/W)	121	Terminal Type	3 pole piano key
LED			
CCT (K)	3000		
CRI	80		
Macadam Elipses	4		

Order Code: XCSBT417WW

17W - 1200mm Batten - 3000K

Dimensions

A (mm)	1200
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

