

Order Code: XCSBT435CT
35W - 1200mm Batten CC [3000K/4000K/6000K]



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Up to 123 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry



Technical Data

General		Electrical	
Luminaire Wattage (W)	35	Rated Input Current (A)	0.08
Weight (kg)	1.20	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	8
Lumens (lm)	4300	Surge Protection (kV)	1
Efficacy (lm/W)	123	Conductor Size (mm)	1.5
LED		Terminal Type	3 pole piano key
CCT (K)	TRI-COLOUR		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	800		
Forward Voltage (V)	24-42		

Order Code: XCSBT435CT
35W - 1200mm Batten CC [3000K/4000K/6000K]

Dimensions

A (mm)	1200
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

