

Order Code: XCSBT435CTM3

35W - 1200mm Batten CC [3000K/4000K/6000K] - 3hrs Maintained Emergency

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Up to 123 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry

Technical Data**General**

Luminaire Wattage (W)	35
Weight (kg)	1.60
Operating Temperature (ta °C)	5 to 25

Light Output

Lumens (lm)	4300
Efficacy (lm/W)	123

LED

CCT (K)	TRI-COLOUR
CRI	80
Macadam Ellipses	4

Driver

Driver Current (mA)	800
Forward Voltage (V)	24-42

Emergency

Emergency Lumen Operating	190
Emergency Wattage (W)	1

Order Code: XCSBT435CTM3

35W - 1200mm Batten CC [3000K/4000K/6000K] - 3hrs Maintained Emergency

Dimensions

A (mm)	1200
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

