

Order Code: XCSBT435NWP

35W - 1200mm Batten - 4000K - PIR

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 114 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Loop in/out mains connector
- Integral emergency option available
- Integral high quality driver and LED module
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

Technical Data**General**

Luminaire Wattage (W)	35
Weight (kg)	1.00
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	4000
Efficacy (lm/W)	114

LED

CCT (K)	4000
CRI	80
Macadam Ellipses	4

Electrical

Rated Input Current (A)	0.16
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	3 pole piano key

Order Code: XCSBT435NWP

35W - 1200mm Batten - 4000K - PIR

Dimensions

A (mm)	1321
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

