xcite LED Lighting
Data Sheet

Order Code: XCSBT518NW

18W - 1500mm Batten - 4000K



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Batten fit PIR option available
- Up to 133 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

3000K 4000K 6000K 50,000 HOURS 5YRS WARRANTY ONSITE 1 WARRANTY IP20 IK06 M3

Technical Data

General

Luminaire Wattage (W)	18
Weight (kg)	1.10
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	2400
Efficacy (lm/W)	133

LED

CCT (K)	4000
CRI	80
Macadam Elipses	4

Electrical

Rated Input Current (A)	0.09
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	8
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	3 pole piano key

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet


Order Code: XCSBT518NW

18W - 1500mm Batten - 4000K

Dimensions

Length (mm)	1500
Width (mm)	55
Depth (mm)	58
Fix	610

Line Drawing



Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk