## xcite LED Lighting

### **Data Sheet**



Order Code: XCSBT518NWM3P

18W - 1500mm Batten - 4000K - 3hrs Maintained Emergency - PIR



### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 133 lumens per watt efficacy

#### Construction

- Steel body in white finish
- · High quality opal diffuser to reduce glare
- · Loop in/out mains connector
- Integral emergency option available
- Integral high quality driver and LED module
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]























### **Technical Data**

Toolinical Data			
General		Electrical	
Luminaire Wattage (W)	18	Rated Input Current (A)	0.09
Weight (kg)	1.60	Power Factor (pf)	0.9
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output  Lumens (Im) 240		Inrush Current Peak (A)	8
	2400	Surge Protection (kV)	1
Efficacy (lm/W)	133	Conductor Size (mm)	1.5
Lineacy (mi/wy)		Terminal Type	4 pole piano key
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Emergency			
Emergency Lumen Operating	190		
Emergency Wattage (W)	1		

# xcite LED Lighting

### **Data Sheet**



### Order Code: XCSBT518NWM3P

18W - 1500mm Batten - 4000K - 3hrs Maintained Emergency - PIR

#### **Dimensions**

A (mm)	1621
B (mm)	55
C (mm)	58
Fix	610

### Line Drawing



