

Order Code: XCSBT528DLM3

28W - 1500mm Batten - 6000K - 3hrs Maintained Emergency

Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Batten fit PIR option available
- Up to 125 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Loop in/out mains connector
- Integral high quality driver and LED module
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W) | 28 | Rated Input Current (A) | 0.13 |
| Weight (kg) | 1.50 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | 5 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Inrush Current Peak (A) | 10 |
| | | Surge Protection (kV) | 1 |
| | | Conductor Size (mm) | 1.5 |
| | | Terminal Type | 4 pole piano key |
| Light Output | | | |
| Lumens (lm) | 3500 | | |
| Efficacy (lm/W) | 125 | | |
| LED | | | |
| CCT (K) | 6000 | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |
| Emergency | | | |
| Emergency Lumen Operating | 190 | | |
| Emergency Wattage (W) | 1 | | |

Order Code: XCSBT528DLM3

28W - 1500mm Batten - 6000K - 3hrs Maintained Emergency

Dimensions

| | |
|--------|------|
| A (mm) | 1500 |
| B (mm) | 55 |
| C (mm) | 58 |
| Fix | 610 |

Line Drawing

