# xcite LED Lighting

## **Data Sheet**

Order Code: XCSBT528NWP 28W - 1500mm Batten - 4000K - PIR



### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 125 lumens per watt efficacy

#### Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral emergency option available
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight





















Macadam Elipses



## **Technical Data**

General		Electrical	
Luminaire Wattage (W)	28	Rated Input Current (A)	0.13
Weight (kg)	1.20	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Links Outron		Inrush Current Peak (A)	10
Light Output  Lumens (Im)	3500	Surge Protection (kV)	1
Efficacy (Im/W)	125	Conductor Size (mm)	1.5
		Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		

# xcite LED Lighting

# **Data Sheet**



Order Code: XCSBT528NWP 28W - 1500mm Batten - 4000K - PIR

#### **Dimensions**

A (mm)	1621
B (mm)	55
C (mm)	58
Fix	610

## Line Drawing



