

Order Code: XCSBT528WWP
28W - 1500mm Batten - 3000K - Batten fit PIR



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Batten fit PIR option available
- Up to 120 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

3000K 4000K 6000K 30,000 HOURS 5YRS WARRANTY ONSITE WARRANTY 1 IP20 IK06 M3

Technical Data

General		Electrical	
Luminaire Wattage (W)	28	Rated Input Current (A)	0.13
Weight (kg)	1.20	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	10
Lumens (lm)	3350	Surge Protection (kV)	1
Efficacy (lm/W)	120	Conductor Size (mm)	1.5
LED		Terminal Type	3 pole piano key
CCT (K)	3000		
CRI	80		
Macadam Elipses	4		

Order Code: XCSBT528WWP

28W - 1500mm Batten - 3000K - Batten fit PIR

Dimensions	
A (mm)	1621
B (mm)	55
C (mm)	58
Fix	610

