

Order Code: XCSBT631NWP
31W - 1800mm Batten - 4000K - PIR



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 131 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral emergency option available
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



Technical Data

General		Electrical	
Luminaire Wattage (W)	31	Rated Input Current (A)	0.14
Weight (kg)	1.40	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	10
Lumens (lm)	4050	Surge Protection (kV)	1
Efficacy (lm/W)	131	Conductor Size (mm)	1.5
LED		Terminal Type	3 pole piano key
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		

Order Code: XCSBT631NWP
31W - 1800mm Batten - 4000K - PIR

Dimensions

A (mm)	1921
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

