

Order Code: XCSBT660CT

60W - 1800mm Batten CC [3000K/4000K/6000K]



Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Up to 123 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry

Technical Data

General

Luminaire Wattage (W)	60
Weight (kg)	1.70
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	7400
Efficacy (lm/W)	123

LED

CCT (K)	TRI-COLOUR
CRI	80
Macadam Ellipses	4

Driver

Driver Current (mA)	1400
Forward Voltage (V)	24-42

Electrical

Rated Input Current (A)	0.14
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	3 pole piano key

Order Code: XCSBT660CT

60W - 1800mm Batten CC [3000K/4000K/6000K]

Dimensions

A (mm)	1800
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

