# xcite LED Lighting

## **Data Sheet**



Order Code: XCSBT660HONWP

60W - 1800mm Batten - 4000K - High Output - PIR



### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 170 lumens per watt efficacy

#### Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Integral emergency option available
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



















CRI

Macadam Elipses





## **Technical Data**

| General                       |         | Electrical                |                  |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W)         | 60      | Rated Input Current (A)   | 0.27             |
| Weight (kg)                   | 1.40    | Power Factor (pf)         | 0.9              |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240          |
| Light Output  Lumens (Im)     |         | Inrush Current Peak (A)   | 13               |
|                               | 10000   | Surge Protection (kV)     | 1                |
| Efficacy (Im/W)               | 170     | Conductor Size (mm)       | 1.5              |
|                               |         | Terminal Type             | 3 pole piano key |
| LED                           |         |                           |                  |
| CCT (K)                       | 4000    |                           |                  |

>80

## xcite LED Lighting

## **Data Sheet**



Order Code: XCSBT660HONWP

60W - 1800mm Batten - 4000K - High Output - PIR

#### **Dimensions**

| A (mm) | 1921 |
|--------|------|
| B (mm) | 55   |
| C (mm) | 58   |
| Fix    | 610  |

### Line Drawing



