

Order Code: XCSBT660HONWP
60W - 1800mm Batten - 4000K - High Output - PIR



Features

- Ideal for replacement of linear fluorescent fixtures
• Suitable for general domestic and commercial use
• Available with PIR [VB1T] or PIR & Photocell [VB2T]
• Up to 170 lumens per watt efficacy

Construction

- Steel body in white finish
• High quality opal diffuser to reduce glare
• Integral emergency option available
• Integral high quality driver and LED module
• Loop in/out mains connector
• Conduit and BESA fixing points for end or rear cable entry
• Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



Technical Data

Table with 2 main sections: General and Electrical. General includes Luminaire Wattage (60W), Weight (1.40kg), Operating Temperature (0 to 25°C), Light Output (10000 lumens, 170 lm/W), and LED (4000K CCT, >80 CRI, 4 Macadam Elipses). Electrical includes Rated Input Current (0.27A), Power Factor (0.9), Input Voltage Range (220-240V), Inrush Current Peak (13A), Surge Protection (1kV), Conductor Size (1.5mm), and Terminal Type (3 pole piano key).

Order Code: XCSBT660HONWP

60W - 1800mm Batten - 4000K - High Output - PIR

Dimensions

A (mm)	1921
B (mm)	55
C (mm)	58
Fix	610

Line Drawing

