# xcite LED Lighting

## **Data Sheet**

Order Code: XCSBT660NWP 60W - 1800mm Batten - 4000K - PIR



### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 128 lumens per watt efficacy

#### Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Loop in/out mains connector
- Integral emergency option available
- Integral high quality driver and LED module
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]





















Macadam Elipses



## **Technical Data**

General		Electrical	
Luminaire Wattage (W)	60	Rated Input Current (A)	0.27
Weight (kg)	1.40	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	13
Light Output Lumens (Im)	7650	Surge Protection (kV)	1
Efficacy (Im/W)	128	Conductor Size (mm)	1.5
		Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		

# xcite LED Lighting

# **Data Sheet**



Order Code: XCSBT660NWP 60W - 1800mm Batten - 4000K - PIR

#### **Dimensions**

A (mm)	1921
B (mm)	55
C (mm)	58
Fix	610

### Line Drawing



