

Order Code: XCSC15NW

15W - Scoop Adjustable Downlight - 4000K



Features

- Suitable for retail and display areas
- Fully adjustable up to 350° rotation and 45° tilt
- Supplied with polished aluminium reflector - 35° beam angle
- Up to 100 lumens per watt efficacy

Construction

- Die-cast aluminium body finished in white
- Remote driver
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	15	Rated Input Current (A)	0.09
Weight (kg)	0.46	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-10 to 40	Input Voltage Range (VAC)	220 - 240
		Inrush Current Peak (A)	3.76
		Surge Protection (kV)	0.5
		Conductor Size (mm)	1.5
		Terminal Type	2-pole screw down
Light Output			
Lumens (lm)	1500		
Efficacy (lm/W)	100		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	24 - 40		

Order Code: XCSC15NW

15W - Scoop Adjustable Downlight - 4000K

Dimensions

C (mm)	94

Cut Out (mm)	105

Dia. (mm)	113

Line Drawing

