

**Order Code: XCSC15NW**

15W - Scoop Adjustable Downlight - 4000K



**Features**

- Suitable for retail and display areas
- Fully adjustable up to 350° rotation and 45° tilt
- Supplied with polished aluminium reflector - 35° beam angle
- Up to 100 lumens per watt efficacy

**Construction**

- Die-cast aluminium body finished in white
- Remote driver
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	15	Rated Input Current (A)	0.09
Weight (kg)	0.46	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-10 to 40	Input Voltage Range (VAC)	220 - 240
<b>Light Output</b>		Inrush Current Peak (A)	3.76
Lumens (lm)	1500	Surge Protection (kV)	0.5
Efficacy (lm/W)	100	Conductor Size (mm)	1.5
<b>LED</b>		Terminal Type	2-pole screw down
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
<b>Driver</b>			
Driver Current (mA)	350		
Forward Voltage (V)	24 - 40		

**Order Code: XCSC15NW**

15W - Scoop Adjustable Downlight - 4000K

### Dimensions

C (mm)	94
Cut Out (mm)	105
Dia. (mm)	113

### Line Drawing

