xcite LED Lighting

Data Sheet



Order Code: XCSC15NW

15W - Scoop Adjustable Downlight - 4000K



Features

- Suitable for retail and display areas
- Fully adjustable up to 350° rotation and 45° tilt
- Supplied with polished aluminium reflector 35° beam angle
- Up to 100 lumens per watt efficacy

Construction

- Die-cast aluminium body finished in white
- Remote driver
- Supplied as standard with neutral white [4000K] LED













Technical Data

	General		
Luminaire Wattage (W)	15	Rated Input Current (A)
Weight (kg)		0.46	Power Factor (pf)
Operating Temperature (ta °C)		-10 to 40	Input Voltage Range (VAC
			Inrush Current Peak (A)
Lumens (lm)	Light Output		Surge Protection (kV)
Efficacy (lm/W)		1500 100	Conductor Size (mm)
			Terminal Type
	LED		
CCT (K)		4000	
CRI		80	
Macadam Elipses		4	
	Driver		
Driver Current (mA)		350	
Forward Voltage (V)		24 - 40	

Electrical			
Rated Input Current (A)	0.09		
Power Factor (pf)	0.9		
Input Voltage Range (VAC)	220 - 240		
Inrush Current Peak (A)	3.76		
Surge Protection (kV)	0.5		
Conductor Size (mm)	1.5		
Terminal Type	2-pole screw down		

xcite LED Lighting

Data Sheet




Order Code: XCSC15NW

15W - Scoop Adjustable Downlight - 4000K

Dimensions

C (mm)	94
Cut Out (mm)	105
Dia. (mm)	113

Line Drawing



Dia

