xcite LED Lighting

Data Sheet

Order Code: XCSC40NW

40W - Scoop Adjustable Downlight - 4000K



Features

- Suitable for retail and display areas
- Fully adjustable up to 350° rotation and 45° tilt
- Supplied with polished aluminium reflector 35° beam angle
- Up to 100 lumens per watt efficacy

Construction

- Die-cast aluminium body finished in white
- Remote driver
- Supplied as standard with neutral white [4000K] LED















Technical Data

Technical Data				
General		Electrical		
Luminaire Wattage (W)	40	Rated Input Current (A)	0.27	
Weight (kg)	1.14	Power Factor (pf)	0.9	
Operating Temperature (ta °C)	-10 to 40	Input Voltage Range (VAC)	220 - 240	
Light Output Lumens (Im)		Inrush Current Peak (A)	24.9	
	4000	Surge Protection (kV)	1	
Efficacy (Im/W)	100	Conductor Size (mm)	1.5	
		Terminal Type	2-pole screw down	
LED				
CCT (K)	4000			
CRI	80			
Macadam Elipses	4			
Driver				
Driver Current (mA)	950			
Forward Voltage (V)	24 - 42			

xcite LED Lighting

Data Sheet




Order Code: XCSC40NW

40W - Scoop Adjustable Downlight - 4000K

Dimensions

C (mm)	145
Cut Out (mm)	155
Dia. (mm)	163

Line Drawing



Dia

