xcite LED Lighting
Data Sheet

Order Code: XCSEBM3

3W - Emergency Slimline Exit Box with Arrow Up Legend - 3hrs Maintained Emergency



Features

- Suitable for open areas and escape routes
- Rear BESA fix and 3 additional rear fixing points
- Reduced maintenance and high performance
- Only 30mm depth for modern, slimline appearance
- Dual LED array for internal illumination and downward distribution
- Test switch fitted for easy testing
- EURO 1,2 & 4 running man legend also available [sold separately]

Construction

- Plastic body
- Hinged front lid for easy installation

50,000 HOURS | 3YRS WARRANTY | IP20 | IK06 | M3

Technical Data

General

Luminaire Wattage (W)	3.2
Weight (kg)	0.65
Operating Temperature (ta °C)	5 to 25

LED

CCT (K)	6500
CRI	70

Driver

Driver Current (mA)	172
Forward Voltage (V)	2.7

Electrical

Rated Input Current (A)	0.029
Power Factor (pf)	0.46
Input Voltage Range (VAC)	220-240
Conductor Size (mm)	1.5
Terminal Type	4 pole screw down

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Order Code: XCSEBM3

3W - Emergency Slimline Exit Box with Arrow Up Legend - 3hrs Maintained Emergency

Dimensions

Length (mm)	325
Width (mm)	185
Depth (mm)	30

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk