xcite LED Lighting
Data Sheet

Order Code: XCSEDL1NM3

1W - Emergency Downlight - 3hrs Non-maintained Emergency - Surface Mounted



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Very low energy consumption - 1W

Construction

- Polycarbonate body
- Operates in non-maintained mode
- Separate high quality LED driver
- Internal mains connection

50,000 HOURS | 3YRS WARRANTY | IP20 | IK06 | NM3

Technical Data

General

Luminaire Wattage (W)	1
Weight (kg)	0.37
Operating Temperature (ta °C)	5 to 25

LED

CCT (K)	6500
CRI	60

Emergency

Emergency Lumen Operating	120
Emergency Wattage (W)	1

Electrical

Conductor Size (mm)	1.5
Terminal Type	3 pole screw down

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet

Order Code: XCSEDL1NM3

1W - Emergency Downlight - 3hrs Non-maintained Emergency - Surface Mounted

Dimensions

Length (mm)	170
Width (mm)	120
Depth (mm)	45

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk