

Order Code: XCSEDL1NM3

1W - Emergency Downlight - 3hrs Non-maintained Emergency - Surface Mounted

Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Very low energy consumption - 1W

Construction

- Polycarbonate body
- Operates in non-maintained mode
- Separate high quality LED driver
- Internal mains connection



Technical Data

General

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 1 |
| Weight (kg) | 0.37 |
| Operating Temperature (ta °C) | 5 to 25 |

Electrical

| | |
|---------------------|-------------------|
| Conductor Size (mm) | 1.5 |
| Terminal Type | 3 pole screw down |

LED

| | |
|---------|------|
| CCT (K) | 6500 |
| CRI | 60 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 120 |
| Emergency Wattage (W) | 1 |

Order Code: XCSEDL1NM3

1W - Emergency Downlight - 3hrs Non-maintained Emergency - Surface Mounted

Dimensions

| | |
|--------|-----|
| A (mm) | 170 |
| B (mm) | 120 |
| C (mm) | 45 |

Line Drawing

