

**Order Code: XCSEDL1NM3C**

1W - Emergency Downlight - 3hrs Non-maintained Emergency - Surface Mounted - Corridor Version

**Features**

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Very low energy consumption - 1W

**Construction**

- Polycarbonate body
- Operates in non-maintained mode
- Separate high quality LED driver
- Internal mains connection



**Technical Data**

**General**

|                               |         |
|-------------------------------|---------|
| Luminaire Wattage (W)         | 1       |
| Weight (kg)                   | 0.37    |
| Operating Temperature (ta °C) | 5 to 25 |

**Electrical**

|                     |                   |
|---------------------|-------------------|
| Conductor Size (mm) | 1.5               |
| Terminal Type       | 3 pole screw down |

**LED**

|         |      |
|---------|------|
| CCT (K) | 6500 |
| CRI     | 60   |

**Emergency**

|                           |     |
|---------------------------|-----|
| Emergency Lumen Operating | 105 |
| Emergency Wattage (W)     | 1   |

**Order Code:** XCSEDL1NM3C

1W - Emergency Downlight - 3hrs Non-maintained Emergency - Surface Mounted - Corridor Version

### Dimensions

|        |     |
|--------|-----|
| A (mm) | 170 |
| B (mm) | 120 |
| C (mm) | 45  |

### Line Drawing

