xcite LED Lighting

Data Sheet



Order Code: XCSEDL1NM3CST

1W - Fixed Output - Non-maintained Emergency Self-test - Corridor Function - 6500K



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- Virtually service free emergency lighting
- Easy to install with simple connection wiring

Construction

- Very low energy consumption 1W
- Polycarbonate body
- Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance













Technical Data

General		
Luminaire Wattage (W)	1	F
Weight (kg)	0.37	I
Operating Temperature (ta °C)		(
LED		1
CCT (K)	6500	
CRI	70	
Driver		
Driver Current (mA)	350	
Forward Voltage (V)	2.1	
Emergency		
Emergency Lumen Operating	140	
Emergency Wattage (W)	1	

Electrical	
Rated Input Current (A)	0.035
Input Voltage Range (VAC)	220-240
Conductor Size (mm)	1.5
Terminal Type	3 pole screw down



xcite LED Lighting

Data Sheet



Order Code: XCSEDL1NM3CST

1W - Fixed Output - Non-maintained Emergency Self-test - Corridor Function - 6500K

Dimensions

A (mm)	170
B (mm)	120
C (mm)	45

Line Drawing



