xcite LED Lighting

Data Sheet



Order Code: XCSEDL1NM3ST

1W - Fixed Output - Non-maintained Emergency Self-test - 6500K



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- · Virtually service free emergency lighting
- Easy to install with simple connection wiring

Construction

- Very low energy consumption 1W
- Polycarbonate body
- Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance













Technical Data

General	
Luminaire Wattage (W)	1
Weight (kg)	0.37
Operating Temperature (ta °C)	
LED	
CCT (K)	6500
CRI	70
Driver	
Driver Current (mA)	350
Forward Voltage (V)	3.1
Emergency	
Emergency Lumen Operating	140
Emergency Wattage (W)	1

Electrical	
Rated Input Current (A)	0.035
Input Voltage Range (VAC)	220-240
Conductor Size (mm)	1.5
Terminal Type	3 pole screw down



xcite LED Lighting

Data Sheet



Order Code: XCSEDL1NM3ST

1W - Fixed Output - Non-maintained Emergency Self-test - 6500K

Dimensions

A (mm)	170
B (mm)	120
C (mm)	45

Line Drawing



