

**Order Code: XCSEDLA1NM3ST**

XCITE EM SURFACE DOWNLIGHT ST XCSEDLA - 6500K - Fixed output - non-maintained Emergency Self-test

**Features**

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Supplied with LiFePO4 battery

**Construction**

- Very low energy consumption - 1W
- Polycarbonate body
- Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance



**Technical Data**

| General                       |           | Electrical                |                   |
|-------------------------------|-----------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 2         | Rated Input Current (A)   | 0.02              |
| Weight (kg)                   | 0.30      | Power Factor (pf)         | 0.19              |
| Operating Temperature (ta °C) | 5° to 25° | Input Voltage Range (VAC) | 220 to 240        |
|                               |           | Conductor Size (mm)       | 1.5               |
|                               |           | Terminal Type             | 3 pole screw down |
| LED                           |           |                           |                   |
| CRI                           | 70        |                           |                   |
| Macadam Elipses               | 3.9       |                           |                   |
| Driver                        |           |                           |                   |
| Driver Current (mA)           | 350       |                           |                   |
| Forward Voltage (V)           | 3.1       |                           |                   |
| Emergency                     |           |                           |                   |
| Emergency Lumen Operating     | 130       |                           |                   |
| Emergency Wattage (W)         | 1         |                           |                   |

**Order Code:** XCSEDLA1NM3ST

XCITE EM SURFACE DOWNLIGHT ST XCSEDLA - 6500K - Fixed output - non-maintained Emergency Self-test

Dimensions

|        |     |
|--------|-----|
| A (mm) | 170 |
| B (mm) | 120 |
| C (mm) | 45  |

Line Drawing

