xcite LED Lighting

Data Sheet



1.1 0.9

120

3 pole screw down

Order Code: XCSF100WW

100W - High Output Slim Floodlight - IP65 - 3000K - Black





- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 83 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation





Macadam Elipses









Technical Data

General		Electrical
Luminaire Wattage (W)	100	Rated Input Current (A)
Weight (kg)	4.80	Power Factor (pf)
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)
Light Output Lumens (Im)		Inrush Current Peak (A)
	8300	Surge Protection (kV)
Efficacy (Im/W)	83	Conductor Size (mm)
		Terminal Type
LED		
CCT (K)	3000	
CRI	65	

xcite LED Lighting

Data Sheet



Order Code: XCSF100WW

100W - High Output Slim Floodlight - IP65 - 3000K - Black

Dimensions

A (mm)	415
B (mm)	310
C (mm)	88

Line Drawing



