

Order Code: XCSF10WWP
10W - High Output Slim Floodlight - IP65 - PIR - 3000K - Black



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 70 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation



Technical Data

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.045
Weight (kg)	0.60	Power Factor (pf)	0.8
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100-240
Light Output		Inrush Current Peak (A)	30
Lumens (lm)	700	Surge Protection (kV)	0.5
Efficacy (lm/W)	70	Conductor Size (mm)	1.5
LED		Terminal Type	3 pole screw down
CCT (K)	3000		
CRI	65		
Macadam Elipses	4		

Order Code: XCSF10WWP

10W - High Output Slim Floodlight - IP65 - PIR - 3000K - Black

Dimensions

A (mm)	205
B (mm)	110
C (mm)	52

Line Drawing

