xcite LED Lighting

Data Sheet



Order Code: XCSF150NW

150W - High Output Slim Floodlight - IP65 - 4000K - Black





- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface
- Weatherproof IP65 construction
- Up to 102 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation





Macadam Elipses









Technical Data

General		Electrical		
Luminaire Wattage (W)	150	Rated Input Current (A)	0.9	
Weight (kg)	5.30	Power Factor (pf)	0.9	
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100-305	
Light Output Lumens (Im) 15		Inrush Current Peak (A)	65	
	15300	Surge Protection (kV)	1	
Efficacy (lm/W)	102	Conductor Size (mm)	1.5	
Lineary (in in i	102	Terminal Type	3 pole screw down	
LED				
CCT (K)	4000			
CRI	65			



xcite LED Lighting

Data Sheet



Order Code: XCSF150NW

150W - High Output Slim Floodlight - IP65 - 4000K - Black

Dimensions

A (mm)	485
B (mm)	325
C (mm)	110

Line Drawing



