

**Order Code: XCSF150WW**

150W - High Output Slim Floodlight - IP65 - 3000K - Black



**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 90 lumens per watt efficacy

**Construction**

- White or black body finish
- Breather gland for reducing condensation



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	150	Rated Input Current (A)	0.9
Weight (kg)	5.30	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100-305
		Inrush Current Peak (A)	65
		Surge Protection (kV)	1
		Conductor Size (mm)	1.5
		Terminal Type	3 pole screw down
Light Output			
Lumens (lm)	13400		
Efficacy (lm/W)	90		
LED			
CCT (K)	3000		
CRI	65		
Macadam Elipses	4		

**Order Code: XCSF150WW**

150W - High Output Slim Floodlight - IP65 - 3000K - Black

Dimensions

A (mm)	485
B (mm)	325
C (mm)	110

Line Drawing

