xcite LED Lighting

Data Sheet



Order Code: XCSF30NWW

30W - High Output Slim Floodlight - IP65 - 4000K - White



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 90 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation













Technical Data

30	Rated Inp
4.04	Power Fa
	Input Volt
	Inrush Cu
2700	Surge Pro
	Conducto
	Terminal
4000	
65	
4	
	1.61 -20 to 25 2700 90 4000 65

Electrical		
Rated Input Current (A)	0.13	
Power Factor (pf)	0.9	
Input Voltage Range (VAC)	100-240	
Inrush Current Peak (A)	90	
Surge Protection (kV)	1	
Conductor Size (mm)	1.5	
Terminal Type	3 pole screw down	

xcite LED Lighting

Data Sheet



Order Code: XCSF30NWW

30W - High Output Slim Floodlight - IP65 - 4000K - White

Dimensions

A (mm)	305
B (mm)	190
C (mm)	64

Line Drawing



