

Order Code: XCSF50NW
50W - High Output Slim Floodlight - IP65 - 4000K - Black



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 94 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation



Technical Data

| General                       |           | Electrical                |                   |
|-------------------------------|-----------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 50        | Rated Input Current (A)   | 0.2               |
| Weight (kg)                   | 2.48      | Power Factor (pf)         | 0.9               |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 100-240           |
| Light Output                  |           | Inrush Current Peak (A)   | 90                |
| Lumens (lm)                   | 4700      | Surge Protection (kV)     | 1                 |
| Efficacy (lm/W)               | 94        | Conductor Size (mm)       | 1.5               |
| LED                           |           | Terminal Type             | 3 pole screw down |
| CCT (K)                       | 4000      |                           |                   |
| CRI                           | 65        |                           |                   |
| Macadam Elipses               | 4         |                           |                   |

**Order Code:** XCSF50NW  
50W - High Output Slim Floodlight - IP65 - 4000K - Black

Dimensions

|        |     |
|--------|-----|
| A (mm) | 355 |
| B (mm) | 235 |
| C (mm) | 70  |

Line Drawing

