

### Order Code: XCSF50NWP

50W - High Output Slim Floodlight - IP65 - PIR - 4000K - Black



### Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 94 lumens per watt efficacy

### Construction

- White or black body finish
- Breather gland for reducing condensation



### Technical Data

General		Electrical	
Luminaire Wattage (W)	50	Rated Input Current (A)	0.2
Weight (kg)	2.56	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100-240
		Inrush Current Peak (A)	90
		Surge Protection (kV)	1
		Conductor Size (mm)	1.5
		Terminal Type	3 pole screw down
Light Output			
Lumens (lm)	4700		
Efficacy (lm/W)	94		
LED			
CCT (K)	4000		
CRI	65		
Macadam Elipses	4		

**Order Code: XCSF50NWP**

50W - High Output Slim Floodlight - IP65 - PIR - 4000K - Black

Dimensions

A (mm)	360
B (mm)	235
C (mm)	70

Line Drawing

