

**Order Code: XCSF50NWPW**

50W - High Output Slim Floodlight - IP65 - PIR - 4000K - White

**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 94 lumens per watt efficacy

**Construction**

- White or black body finish
- Breather gland for reducing condensation

**Technical Data****General**

|                               |           |
|-------------------------------|-----------|
| Luminaire Wattage (W)         | 50        |
| Weight (kg)                   | 2.56      |
| Operating Temperature (ta °C) | -20 to 25 |

**Light Output**

|                 |      |
|-----------------|------|
| Lumens (lm)     | 4700 |
| Efficacy (lm/W) | 94   |

**LED**

|                  |      |
|------------------|------|
| CCT (K)          | 4000 |
| CRI              | 65   |
| Macadam Ellipses | 4    |

**Electrical**

|                           |                   |
|---------------------------|-------------------|
| Rated Input Current (A)   | 0.2               |
| Power Factor (pf)         | 0.9               |
| Input Voltage Range (VAC) | 100-240           |
| Inrush Current Peak (A)   | 90                |
| Surge Protection (kV)     | 1                 |
| Conductor Size (mm)       | 1.5               |
| Terminal Type             | 3 pole screw down |

### Order Code: XCSF50NWPW

50W - High Output Slim Floodlight - IP65 - PIR - 4000K - White

#### Dimensions

|        |     |
|--------|-----|
| A (mm) | 360 |
| B (mm) | 235 |
| C (mm) | 70  |

#### Line Drawing

